

## COOPER &amp; DUNHAM LLP

ATTORNEYS AT LAW

30 ROCKEFELLER PLAZA, NEW YORK, NEW YORK 10112

TELEPHONE: (212) 278-0400

IVAN S. KAVRUKOV  
 PETER O. MURRAY  
 WILLIAM E. PELTON  
 ERIC D. NIMBCH  
 RARY J. BERSHIK  
 ROBERT T. MALDONADO  
 RICHARD F. JAWORSKI  
 TONIA A. SAYOUR  
 KIMMY OYM  
 LETITIA A. DEGRASSI  
 JENNIFER RAK  
 CINDY S. SHU

NORMAN H. EVIN  
 JOHN P. WHITE  
 ROBERT D. KATZ  
 PAUL TENG  
 WENDY E. MILLER  
 RICHARD S. MILLER  
 BRIAN J. AMOS  
 BRENDAN J. CARBO  
 MIN ("MICHAEL") LIN  
 ENYINNAYA V. OBI  
 LENN HONG

FACSIMILE: (212) 391-0525  
 (212) 391-0626  
 (212) 391-0630

OF COUNSEL  
 CHRISTOPHER C. DUNHAM

SCIENTIFIC ADVISORS  
 JACK ROSA, PH.D.  
 LUIS MUNIZ, PH.D.  
 RAYMOND CHUNG, PH.D.

REGISTERED PATENT AGENTS  
 ANDREW CHUNG, S.E.  
 ELISA Y. KIM, S.A.

FOUNDED 1887  
 www.cooperdunham.com

NEW YORK STATE BAR ADMISSION PENDING

## FACSIMILE TRANSMISSION

## PLEASE DELIVER THE FOLLOWING PAGES

TO : United States Patent and Trademark Office  
 ATTN: Examiner Richard Z. Zhu, Group Art Unit 2625  
 FAX NO.: (571) 270-2587  
 FROM: Paul Teng OUR DOCKET NO.: 2271/71523  
 DATE : February 20, 2009

TOTAL NUMBER OF PAGES, INCLUDING COVER SHEET: 3

IF YOU DO NOT RECEIVE ALL THE PAGES, PLEASE CALL BACK AS SOON AS POSSIBLE TO (212) 278-0400.

MESSAGE

Examiner Zhu,

Attached is proposed claim amendments, as discussed in connection with Serial No. 10/763,707. If all is in order please enter by Examiner's Amendment to place application in condition for allowance.

Thank you.

Paul Teng, Reg. No. 40,837

THE INFORMATION CONTAINED IN THIS FACSIMILE TRANSMISSION IS INTENDED SOLELY FOR THE PERSONAL AND CONFIDENTIAL USE OF THE DESIGNATED RECIPIENT(S) NAMED ABOVE. THIS TRANSMISSION MAY BE AN ATTORNEY-CLIENT COMMUNICATION CONTAINING INFORMATION THAT IS PRIVILEGED AND CONFIDENTIAL. IF THE READER OF THIS MESSAGE IS NOT A DESIGNATED RECIPIENT OR AN AGENT RESPONSIBLE FOR DELIVERING IT TO A DESIGNATED RECIPIENT, YOU ARE HEREBY NOTIFIED THAT YOU HAVE RECEIVED THIS DOCUMENT IN ERROR, AND THAT ANY REVIEW, DISTRIBUTION, OR COPYING OF THIS MESSAGE IS STRICTLY PROHIBITED. IF YOU HAVE RECEIVED THIS COMMUNICATION IN ERROR, OR IF UPON READING THIS DOCUMENT YOU HAVE REASON TO BELIEVE THAT THE DOCUMENT WAS INADVERTENTLY SENT TO YOU, PLEASE NOTIFY US IMMEDIATELY BY COLLECT TELEPHONE CALL AND RETURN THE ORIGINAL MESSAGE TO US BY MAIL. THANK YOU.

Masashi TOKUDA, S.N. 10/763,707

Dkt. 2271/71523

## 1. A facsimile use modem apparatus, comprising:

an analog interface formed from a silicon data access arrangement operative to interface with an analog telephone line, said analog interface including an insulation device configured to insulate a remainder of said facsimile use modem apparatus from said analog telephone line;

a digital interface operative to interface with an ISDN (integrated services digital network) line and configured for G3 communications through the ISDN line;

a signal converting device configured to convert a modem signal used in facsimile communications via the analog telephone line into a first signal used in the ISDN line, and convert a second signal from the ISDN line into a converted signal for use in facsimile communications via the analog telephone line;

a monitoring device located within the silicon data access arrangement and configured for monitoring a progress of the facsimile communications via the ISDN line; [[and]]

a data transmitting device operative to transmit linear data to a speaker via the silicon data access arrangement; and , wherein

a system side device connecting the silicon data access arrangement and the digital interface that enables transmission of signal through an insulation condenser to thereby enable said monitoring device located within the silicon data access arrangement [[is]] and configured for monitoring G3 communications executed through the ISDN line.

## 7. A facsimile apparatus including a facsimile use modem comprising:

an analog interface formed from a silicon data access arrangement operative to interface with an analog telephone line, said analog interface including an insulation device configured to insulate a remainder of said facsimile use modem apparatus from said analog telephone line;

a digital interface operative to interface with an ISDN (integrated services digital network) line and configured for G3 communications through the ISDN line;

a signal converting device configured to convert a modem signal used in facsimile communications via the analog telephone line into a first signal used in the ISDN line, and convert a second signal from the ISDN line into a converted signal for use in facsimile communications via the analog telephone line;

a monitoring device located within the silicon data access arrangement and configured for

Masashi TOKUDA, S.N. 10/763,707

Dkt. 2271/71523

monitoring a progress of the facsimile communications via the ISDN line; and

a data transmitting device operative to transmit linear data to a speaker via the silicon data access arrangement; ~~and~~ ~~wherein~~

a system side device connecting the silicon data access arrangement and the digital interface that enables transmission of signal through an insulation condenser to thereby enable said monitoring device located within the silicon data access arrangement [is] and configured for monitoring G3 communications executed through the ISDN line.

8. A network connecting a facsimile apparatus having a facsimile use modem comprising:

an analog interface formed from a silicon data access arrangement operative to interface with an analog telephone line, said analog interface including an insulation device configured to insulate a remainder of said facsimile use modem apparatus from said analog telephone line;

a digital interface operative to interface with an ISDN (integrated services digital network) line and configured for G3 communications through the ISDN line;

a signal converting device configured to convert a modem signal used in facsimile communications via the analog telephone line into a first signal used in the ISDN line, and convert a second signal from the ISDN line into a converted signal for use in facsimile communications via the analog telephone line;

a monitoring device located within the silicon data access arrangement and configured for monitoring a progress of the facsimile communications via the ISDN line; and

a data transmitting device operative to transmit linear data to a speaker via the silicon data access arrangement; ~~and~~ ~~wherein~~

a system side device connecting the silicon data access arrangement and the digital interface that enables transmission of signal through an insulation condenser to thereby enable said monitoring device located within the silicon data access arrangement [is] and configured for monitoring G3 communications executed through the ISDN line.